#### **CHEMICALS**

### **TRI-FLOW® LUBRICANTS WITH P.T.F.E.**

#### Krylon<sup>®</sup> Industrial Tough Coat<sup>™</sup> Acrylic Enamel Paint

- Features patented EZ Touch fan spray nozzle that requires 50% less finger pressure than most other paint valves
- Ideal for light to heavy duty painting projects, both indoors and outdoors



• Tough, protective coating resists chipping and peeling

Minerallac Part Number	Description	STD PKG	Can Size	Net Fill
37473	OSHA Safety Green	6	16 oz	12 oz
37474	OSHA Black	6	16 oz	12 oz
37475	OSHA White	6	16 oz	12 oz
37476	OSHA Yellow	6	16 oz	12 oz
37477	Semi-Flat Black	6	16 oz	12 oz
37478	Max Flat Black	6	16 oz	12 oz
37479	OSHA Red	6	16 oz	12 oz
37480	OSHA Blue	6	16 oz	12 oz
37481	OSHA Orange	6	16 oz	12 oz

#### Krylon<sup>®</sup> Industrial Quick-Mark<sup>™</sup> Inverted Marking Paint

- Heavy-duty industrial paint
- Fast drying, high solids formula that penetrates and adheres to hot surfaces
- Features exclusive Spray-Thru cap and nonclogging spray tip
- Available in APWA colors and fluorescent colors



Minerallac Part Number	Description	STD PKG	Can Size	Net Fill
37681	Fluorescent Safety Red	6	20 oz	17 oz
37459	Fluorescent Safety Green	6	20 oz	17 oz
37460	Fluorescent Orange	6	20 oz	17 oz
37461	Brilliant White APWA	6	20 oz	17 oz
37462	Utility Yellow APWA	6	20 oz	17 oz
37463	Fluorescent Red/Orange	6	20 oz	17 oz
37465	Fluorescent Caution Blue	6	20 oz	17 oz
37466	Clear	6	20 oz	17 oz
37468	Fluorescent Orange	6	20 oz	17 oz

#### Sprayon<sup>®</sup> Zinc Rich Cold Galvanizing Compound

- Fast drying, high solids, high-performance epoxy based coating
- Provides maximum protection to steel exposed to severe corrosive environments
- Fuses zinc to metal substrates to protect against corrosion
- Equal to or better than hot-dipped galvanizing
- 97% pure zinc dust

Minerallac Part	Description	STD	Can	Net
Number		PKG	Size	Fill
37518	Zinc Rich Cold Galvanizing Compound	6	16 oz	14 oz

#### **Sprayon® Electronic Contact Cleaner**

- Heavy-duty degreaser and quick-drying cleaner
- Ideal for sensitive equipment and precision instruments
- Fast-evaporating and leaves no residue
- For use on non-energized equipment
- Safe on most plastics. K2 rated, NSF registered



- increase part life

Minerallac Pa Number 37514

- - wasps and hornets

  - within 24 hours
  - •

  - EPA registered

PKG	Can Size	Net Fill
pray 12	16 oz	12 oz
12	8 oz	6 oz
5	pray 12	pray 12 16 oz

Minerallac Part Number	Description		TD Kg	Can Size	Net Fill
37506	Electronic Contact Cleaner	1	2	16 oz	11 oz

# **711<sup>®</sup> Protector<sup>™</sup> Lubricant**

- Excellent choice to penetrate, lubricate, demoisturize and inhibit corrosion.
- Ultrathin, greaseless formulation
- Does not attract contaminants
- Safe on plastic surfaces
- H2 rated, NSF registered
- High D.S. 47,000 volts

 Lubricates with oils, additives, and P.T.F.E. to reduce friction and Penetrates inaccessible areas to displace contaminants • Rejects dirt, dust, and other abrasive particles • Effective from -60° to 475° • H2 rated, NSF registered • Offers 10 times as much load capacity as WD-40 in a standard Falex-Load Text (ASTM D-233B)



art	Description	Can Size	Net Fill	
	Industrial Lubricant Aerosol Can	8 oz	6 oz	

#### **INSECT REPELLENTS**

• Contains a high amount of petroleum distillates for the best knockdown and kill rate Residual deposit will kill returning

• Will not harm most plastics • 98% knockdown, 100% kill • D.S. of 33,000 volts Sprays up to 20 feet



#### **SEALANTS**

#### **EZ-Thrust Caulk Gun**

- 10:1 Thrust Ratio
- 1.6 lb unit
- Seal Puncture Tool/Spout Cutter
- Ladder Hook
- EZ Load Front Cap
- Caulk Buddy Included



Minerallac Part Number	Description	STD PKG
96000	EZ-Thrust Caulk Gun	12

#### All Purpose Caulk Gun

- 6:1 Thrust Ratio
- 1.25 lb unit
- Ratchet rod cradle



Minerallac Part Number	Description	STD PKG
96001	Caulk Gun	12

#### White Lightning<sup>®</sup> Silicone Sealant

- Provides a watertight seal
- Use for interior and exterior projects
- Highly, permanently flexible
- Will not crack, crumble or shrink
- Resists moisture and mildew •
- Excellent adhesion to non-porous materials. •
- Not paintable
- NSF compliant
- Complies with TT-S-00230C, TTS-001543A. ASTM C-920

Minerallac Part Number	Description	STD PKG
37530	100% RTV Silicone Sealant – Clear	1
37531	100% RTV Silicone Sealant – White	1



## SEE CATALOG FOR FULL DETAILS www.minerallac.com





# **ESSENTIAL PRODUCTS FOR EVERY JOBSITE KRYLON<sup>®</sup> PAINTS & CHEMICALS**