

59012HSJ

1/4 X 3/4 ZAMAC HAMMER SCREW

UPC: 08593701505

Country of Origin:

UNSPSC: 31162107

TAIWAN

Commodity: Nail expansion anchors



*1/4 x 3/4" Zamac Hammer Screw Anchors, Light Duty
Concrete, Solid Brick Or Block*

Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	"Hammer Drive" Nail-in Anchors
Special Features	A unique one step nail drive anchor featuring a Philips type head and a screw thread for use in concrete, block, brick, or stone. Body is formed from corrosion resistant Zamac Alloy and a zinc plated carbon steel drive screw. Designed to provide a removable anchor with higher tension load capacities compared with traditional nailin when installed in concrete
Application	General purpose anchoring in normal weight concrete, Concrete Masonry, Brick Masonry, and Stone
Size	1/4 X 3/4"
Drill Diameter	1/4"
Minimum Embedment Depth	5/8"
Drive Pin	Removable anchor. Screw can be backed out with Philips head driver
Material	Zamac alloy body with zinc plated carbon steel drive screw
Ultimate Load Capacities (2000 PSI Concrete)	790 lbs Tension, 805 lbs Shear
Allowable Load Capacities (2000 PSI Concrete)	200 lbs Tension, 200 lbs Shear

Compliance Information

Buy America Act Compliant:	No
Buy American Act Compliant:	No
RoHS Compliant:	Yes
UL Compliant:	No
UL Code:	N/A

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Item Status: Active

Standard Qty: 100

Minerallac Company

Tel: 800-927-3293

Fax: 800-824-8942

www.minerallac.com

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product. IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner .