

**59425J**

**10-12x1 GREEN PLASTIC PLUG AN**

UPC: 08593798970  
UNSPSC: 31162101  
Commodity: Concrete anchors

Country of Origin:  
TAIWAN



*#10-12 Green Plastic Plug Anchors, Jar*

## Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Plastic Plug Anchor
Application	Designed for light duty fastening applications in concrete, block, brick or stone. The body of the Fluted Plastic anchor is injection molded from a ductile plastic and is designed to be used with sheet metal or wood screws. These fasteners are not recommended for use overhead or applications where holding values are critical.
Anchor Size	#10-12 x 1"
Color	Green
Drill Diameter	1/4"
Material	Engineered Plastic
Ultimate Load Capacities (2000 PSI Concrete)	440 lbs Tension, 280 lbs Shear
Allowable Load Capacities (2000 PSI Concrete)	110 lbs Tension, 70 lbs Shear

## Compliance Information

Buy America Act Compliant:	No
Buy American Act Compliant:	No
RoHS Compliant:	Yes
UL Compliant:	No
UL Code:	N/A

## Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Item Status:	Active
Standard Qty:	100

## Minerallac Company

Tel: 800-927-3293  
Fax: 800-824-8942  
[www.minerallac.com](http://www.minerallac.com)

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.