

**60405J**

**3/8-16 SHALLOW EMBEDMENT DROP**

UPC: 08593702909

Country of Origin:

UNSPSC: 31162101

CHINA

Commodity: Concrete anchors



*3/8-16 Shallow Embedment Steel Drop-In Anchors,  
Includes Setting Tool, Zinc Plated, Jar*

## Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Mini Dropin expansion anchor
Application	A carbon steel machine bolt anchor designed for use in shallow embedment applications.
Material	Zinc Plated Carbon Steel
Suitable Base Materials	Normal Weight Concrete, Lightweight Concrete, Precast Hollow Core Plank, and Concrete Over Steel Deck
Benefits/ Features	Intertally threaded anchor for easy bolt removability and service work, ideal for precast hollow core plank and post-tensioned concrete slabs, lip provides flush installation and consistent embedment, Manual setting tool scores flange when set to verify proper expansion depth
Rod/ Anchor Diameter	3/8"
Outside Diameter	1/2"
Overall Length	3/4"
Minimum Embedment Depth in.	3/4"
Ultimate Load Capacities (3000 PSI Concrete)	1980 lbs Tension, 2700 lbs Shear
Allowable Load Capacities (3000 PSI Concrete)	495 lbs Tension, 675 lbs Shear

## Compliance Information

Buy America Act Compliant:	No
Buy American Act Compliant:	No
RoHS Compliant:	Yes
UL Compliant:	No
UL Code:	N/A

## Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Item Status: Active

Standard Qty: 100

## Minerallac Company

Tel: 800-927-3293  
Fax: 800-824-8942  
[www.minerallac.com](http://www.minerallac.com)

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner .