

**60434J**

**3/8-16 INTERNAL THRD SCRW ANCR**

UPC: 08593706912

Country of Origin:

UNSPSC: 31161601

IMPORT

Commodity: Anchor bolts



*3/8"-16 Internally Threaded Screw Anchor, Zinc,  
Includes Setting Tool for Quick Install, 50/Jar*

## Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Snake Anchor
Description	The Snake Anchor is an internally threaded, self-tapping screw anchor designed for performance in cracked and uncracked concrete.
General Applications	suspending conduit cable trays and strut, interior low level corrosion enviroment, tension zone/ cracked conrete, Seismic attachments (SDC A-F), Fire sprinklers and pipe supports, suspended lighting
Size	3/8"
Internal Thread Size	3/8"-16
Outside Anchor Diameter	1/2"
Tension Load Capacities (2500 PSI Concrete)	2165 lbs
Shear Load Capacities (2500 PSI Concrete)	1860 lbs
Approvals and Ratings	ICC-ES Listed, Tested in accordance with ACI 355.2 and ICC-ES AC19
Installation	Please note each jar of 50 includes one setting tool

## Compliance Information

Buy America Act Compliant:	No
Buy American Act Compliant:	No
RoHS Compliant:	Yes
UL Compliant:	No
UL Code:	N/A

## Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Item Status:	Active
Standard Qty:	50

## Minerallac Company

Tel: 800-927-3293  
Fax: 800-824-8942  
[www.minerallac.com](http://www.minerallac.com)

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner .