

Product Specification Sheet

96059

FIRESTOP SEALANT 1000+ 5GAL PL

UPC: 08593796059 Country of Origin:

UNSPSC: 46191503

Reso

Commodity: Fire resistant coatings or

putties or sealants

USA

Firestop Caulk 1000+, 5 Gallon Pail, 1ct



Product Attributes	
Brand Name	Minerallac
Sub Brand	Cully
Туре	Firestop Sealant
Description	Metacaulk 1000 is a single component, general purpose fire rated sealant and smoke seal for construction joints and through-penetrations. In the event of a fire, Metacaulk 1000 will prevenet the spread of flames, smoke, hot gases and water through joint openings and through-penetration.
Applications	Metacaulk 1000 can be used in interior applications as a general purpose fire rated sealant and smoke seal for construction joints, through penetrations and blank openings on both vertical and horizontal surfaces. Use Metacaulk 1000 to prevenet the spread of fire and smoke through joints in fire rated gypsum wallboard partitions, concrete block or concrete walls and/ or concrete or corrugated steel deck floor/ ceiling assemblies.
Characteristics/ Features	Water based, excellent freeze-thaw, flexible set, highly intumescent, paintable, VOC compliant, safe and easy to use, 3 year shelf life
Size	5 Gallon Pail

Compliance Information

Buy America Act Compliant: No
Buy American Act Compliant: No
RoHS Compliant: No
UL Compliant: No
UL Code: N/A

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Item Status: Active

Standard Qty:

Minerallac Company

Tel: 800-927-3293 Fax: 800-824-8942 www.minerallac.com

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL

MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.













