

**60410USJ**

**3/4-10 STEEL DROP-IN ANCHOR**

UPC: 08593705810

Country of Origin:

UNSPSC: 31161601

**USA**

Commodity: Anchor bolts



*3/4-10 x 3-1/8" Steel Drop-In Anchors, Includes Setting Tool, Zinc Plated, Jar*

**Product Attributes**

Brand Name	Minerallac
Sub Brand	Cully
Type	Steel Drop-In Anchor
Application	Steel Drop-In Anchor is an all steel anchor for us in solid concrete, lightweight concrete, and concrete-filled steel deck members. The anchors can also be considered for hand stone and solid block base materials.
Uses	Suspending conduit, concrete formwork, fire sprinkler supports, pipe supports, cable trays and strut, suspended lighting
Material	Carbon Steel
Rod/ Anchor Size	3/4"
Outside Diameter	1"
Overall Length	3-3/16"
Minimum Embedment Depth	3-3/16"
Ultimate Load Capacities (2000 PSI Concrete)	8,580 lbs Tension, 15,680 lbs Shear
Allowable Load Capacities (2000 PSI Concrete)	2,145 lbs Tension, 3,920 lbs Shear

**Compliance Information**

Buy America Act Compliant:	Yes
Buy American Act Compliant:	Yes
RoHS Compliant:	Yes
UL Compliant:	No
UL Code:	N/A

**Proposition 65**

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Item Status: Active

Standard Qty: 25

**Minerallac Company**

Tel: 800-927-3293  
Fax: 800-824-8942  
www.minerallac.com

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner .